

HD-CVR-4216S

- Up to 16 cameras with 1080p realtime preview
- Support HDCVI / Analog / IP Video input
- All channel 720P
- HDMI / VGA simultaneous video output
- 4/8/16 channel synchronous realtime playback, GRID interface & smart search
- 3D intelligent positioning with HI-FOCUS PTZ dome camera
- Support 2 SATA HDD up to 8TB, 2 USB2.0
- Multiple network monitoring: Web viewer & VMS



SPECIFICATION



Video Input	16 channel, BNC
Audio Input	1 channel, RCA
Video Recording	720P HDCVI DVR
Hard Disk	2 SATA port, up to 8TB
Processor	Embedded processor
Operating System	Embedded Linux
Two-way Talk	Reuse audio input/output channel 1



SPECIFICATION


User Interface	GUI
Video Output	1 HDMI, 1 VGA
Video Standard	NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
Compression	H.264 / G.711
Video Resolution	720P(1280× 720/1280× 600)/960H(960× 576/960× 480)/D1/ 4CIF(704× 576/704× 480) / CIF(352× 288/352× 240) / QCIF(176× 144/176× 120)
Video Recording	Main Stream: 720P/960H/D1/HD1/2CIF/CIF(1~25/30fps), Extra Stream: CIF/QCIF(1~25/30fps)
Video Display Split	1/4/8/9/16
Privacy Masking	4 rectangular zones (each camera)
Audio Output	1 channel, RCA
Motion Detection	Supports
Video Loss	Supports
Camera Blank	Supports
Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
Recording Mode	Manual, Schedule(Regular(Continuous), MD), Stop
Search Mode	Time/Date, MD & Exact search (accurate to second)
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom
Backup Mode	USB Device / Network
Interface Ports	1 HDMI, 1 VGA, 1 RS485, 2 USB2.0
Max User Account	128 users
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocols	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter
Ethernet	RJ-45 port (10/100M)
Power Supply	DC12V/2A
Power Consumption	10W(without HDD)
Working Temp	-10 ~+55°C / 10~90%RH / 86~106kpa
Dimensions	325mm× 245mm× 45mm
Weight	1.5KG(without HDD)

