

## HD-CVR-5204S

- › Up to 4 cameras with 1080p realtime preview
- › Support HDCVI / Analog / IP Video input
- › All channel 1080P
- › HDMI / VGA simultaneous video output
- › 4 channel synchronous realtime playback, GRID interface & smart search
- › 3D intelligent positioning with HI-FOCUS PTZ dome camera
- › ONVIF Version 2.4 Conformance
- › Support 2 SATA HDD up to 8TB, 2 USB2.0
- › Multiple network monitoring: Web viewer & VMS



### SPECIFICATION



<b>Video Input</b>	4 channel, BNC
<b>Audio Input</b>	1 channel, RCA
<b>Video Recording</b>	1080P HDCVI DVR
<b>Hard Disk</b>	2 SATA port, up to 8TB
<b>Processor</b>	Embedded processor
<b>Operating System</b>	Embedded Linux
<b>Two-way Talk</b>	Reuse audio input/output channel 1



**SPECIFICATION**


<b>User Interface</b>	GUI
<b>Video Output</b>	1 HDMI, 1 VGA
<b>Video Standard</b>	NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
<b>Compression</b>	H.264 / G.711
<b>Video Resolution</b>	1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768, 800 × 600
<b>Video Recording</b>	Main Stream : 1080(1~12/15fps) / 720P/960H / D1 (1~25/30fps), Extra Stream: CIF / QCIF(1~25/30fps), D1 (1~6/7fps)
<b>Video Display Split</b>	1/ 4
<b>Privacy Masking</b>	4 rectangular zones (each camera)
<b>Audio Output</b>	1 channel, RCA
<b>Motion Detection</b>	Supports
<b>Video Loss</b>	Supports
<b>Camera Blank</b>	Supports
<b>Trigger Events</b>	Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
<b>Recording Mode</b>	Manual, Schedule(Regular(Continuous), MD), Stop
<b>Search Mode</b>	Time/Date, MD & Exact search (accurate to second)
<b>Playback</b>	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom
<b>Backup Mode</b>	USB Device / Network
<b>Interface Ports</b>	1 HDMI, 1 VGA, 1 RS485, 2 USB2.0
<b>Max User Account</b>	128 users
<b>Record Interval</b>	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
<b>Smart Phone</b>	iPhone, iPad, Android, Windows Phone
<b>Protocols</b>	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter
<b>Ethernet</b>	RJ-45 port (10/100M)
<b>Power Supply</b>	DC12V/2A
<b>Power Consumption</b>	10W(without HDD)
<b>Working Temp</b>	-10 ~+55°C / 10~90%RH / 86~106kpa
<b>Dimensions</b>	325mm× 245mm× 45mm

