



HD-CVR-5208S

- > Up to 8 cameras with 1080p realtime preview
- > Support HDCVI / Analog / IP Video input
- > All channel 1080P
- > HDMI / VGA simultaneous video output
- ▶ 8 channel synchronous realtime playback, GRID interface & smart search
- ▶ 3D intelligent positioning with HI-FOCUS PTZ dome camera
- > ONVIF Version 2.4 Conformance
- > Support 2 SATA HDD up to 8TB, 2 USB2.0
- > Multiple network monitoring: Web viewer & VMS



Video Input8 channel, BNCAudio Input1 channel, RCAVideo Recording1080P HDCVI DVR

Hard Disk2 SATA port, up to 8TBProcessorEmbedded processorOperating SystemEmbedded Linux

Two-way Talk Reuse audio input/output channel 1







SPECIFICATION



User Interface GUI

Video Output 1 HDMI, 1 VGA

Video Standard NTSC(525Line, 60f/s), PAL(625Line, 50f/s)

Compression H.264 / G.711

Video Resolution $1920 \times 1080, 1280 \times 1024, 1280 \times 720, 1024 \times 768, 800 \times 600$ **Video Recording** Main Stream: $1080(1\sim12/15 \text{fps}) / 720P/960H / D1 (1\sim25/30 \text{fps}),$

Extra Steam:CIF /QCIF(1~25/30fps), D1 (1~6/7fps)

Video Display Split 1/4/8/9

Privacy Masking 4 rectangular zones (each camera)

Audio Output 1 channel, RCA

Motion DetectionSupportsVideo LossSupportsCamera BlankSupports

Trigger Events Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips

Recording ModeManual, Schedule(Regular(Continuous), MD), Stop **Search Mode**Time/Date, MD & Exact search (accurate to second)

Playback Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file,

Next camera, Previous camera, Full screen, Repeat, Shuffle,

Backup, selection, Digital zoom

Backup Mode USB Device / Network

Interface Ports 1 HDMI, 1 VGA, 1 RS485, 2 USB2.0

Max User Account 128 users

Record Interval 1~120 min (default: 60 min), Pre-record: 1~30 sec,

Post-record: 10~300 sec

Smart Phone iPhone, iPad, Android, Windows Phone

Protocols HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS,

PPPOE, DDNS, FTP, IP Filter

Ethernet RJ-45 port (10/100M)

Power Supply DC12V/2A

Power Consumption 10W(without HDD)

Working Temp -10 ~+55°C / 10~90%RH / 86~106kpa

Dimensions 325mm× 245mm× 45mm



